

## PRODUCT TECHNICAL DATA SHEET

Issue: 20/03/2015

29mm Crown Glass Bottle Finish PE Plastic Plug "OBTURATEUR DAP"

## **General Information**

The closure device "Obturateur DAP" is a PE plastic plug suitable for application on 29mm champenoise glass bottle finishes with internal volume of 1/2, 1 and 2 liters, compliant to AFNOR NF H 35-022 et NF H35-029 standards, with function of :

- contribution to liquid and gas tightness, in combination with crown cork, after capping and during the disgorging ("dégorgement")
- collect wine yeast sediments and protect the internal side of the 10mm final section of the bottle neck from impurities deposits.
- orientate and make comfortable the yeast sediments ejection.



## Technical features:

Description:	Plastic plug suitable for application on 29 mm champenoise bottle finishes in compliance with AFNOR NF-H35-022 et NF-H35-029 standards
Diameter of the plug body:	18.15 ± 0.10 mm
Diameter of the plug ring:	19.05 ± 0.15 mm
Diameter of the entry plug	$16.20 \pm 0.20$ mm (base of cone section)
cone:	
Total height:	14.50 ± 0.20 mm
Material:	LDPE (LowDensityPolyEthylene) free of any additive and made only by virgin
	plastic materials (no recycled plastics).
Average weight:	1.02g

## Lab performances and others:

Lab performances and others:	
Food compliance:	Compliant for direct contact with food - Refer to relevant food compliance statement
Environment:	94/62CE compliant - Refer to relevant environmental compliance statement
Conditions for use:	For optimal results on application refer to guideline GUIDE DE L'EMBOUTEILLAGE
	N°3- BOUCHAGE DE TIRAGE ET D'EXPEDITION / doc INE 93/006
Application / performances:	The application, and the related performance of the closure, has to be verified
	at every change in the used materials parameters, with special reference to the
	design of the bottle finish, and the specific closing equipment used. Please
	consult your Pelliconi representative if in doubt.
Storage:	The plugs ("Obturateurs") should be stored in a clean, well ventilated, dry
	place, avoiding direct sunlight, high temperatures, and exposure to volatile
	contaminants, and must not be stacked.
Standard Packaging:	Carton Box with 7.500 plugs, 7 boxes for layer, 6 layers per pallet. For a total
	amount of 315.000 plugs per pallet.
	Carton: dimensions (internal), 475X310X305 mm
	Palette (lot): dimensions 1200 x 1200 x 2080 mm pour 42 cartons
	Other packaging solutions available on demand.

